

3” Submersible Solar Pump, AC110V/DC150V, Plastic Impeller, BLAC

model	max. flow (m ³ /h)	max. head (m)	pump		solar panel		pump diameter (inch)	outlet(inch)
			voltage(v)	power(w)	open circuit voltage(v)	recommended power(kw)		
3BLAC5.2-75-110V/150V-0.75	5.2	75	AC110/DC150	750	180-220	1.0	3	1.25
3BLAC5.5-65-110V/150V-0.75	5.5	65	AC110/DC150	750	180-220	1.0	3	1.25
3BLAC7-46-110V/150V-0.75	7	46	AC110/DC150	750	180-220	1.0	3	1.25
3BLAC3.8-123-110V/150V-1.1	3.8	123	AC110/DC150	1100	180-220	1.36	3	1.25
3BLAC6-84-110V/150V-1.1	6	84	AC110/DC150	1100	180-220	1.36	3	1.25
3BLAC7.5-62-110V/150V-1.1	7.5	62	AC110/DC150	1100	180-220	1.36	3	1.25
3BLAC3.8-155-110V/150V-1.3	3.8	155	AC110/DC150	1300	180-220	1.8	3	1.25
3BLAC3.8-180-110V/150V-1.5	3.8	180	AC110/DC150	1500	180-220	2.0	3	1.25
3BLAC6-125-110V/150V-1.5	6	125	AC110/DC150	1500	180-220	2.0	3	1.25
3BLAC7.5-78-110V/150V-1.5	7.5	78	AC110/DC150	1500	180-220	2.0	3	1.25